

Senscient ELDS™ Series 1000 for Methane Cross Duct (XD)

Overview

This Cross Duct Gas Detector is specific to Natural Gas / Methane (CH₄). The separate transmitter and receiver assemblies are certified for use in potentially explosive atmospheres and can detect CH₄ over distances of 0.5 to 5 metres.


Constructed in high grade corrosion resistant 316L Stainless Steel this device is ideally suited for onshore and offshore, open and enclosed environments. Typically mounted on opposite sides of ventilation ducting and with a genuine speed of response of less than 1 second, this device is ideal for fast shutdown of HVAC dampers or boost air flow rates as required.

With no consumable parts and the patented daily auto-self testing facility; called SimuGas™; the Senscient ELDS™ CH₄ XD cross duct detector offers significant operational cost savings over conventional fixed point & cross duct flammable gas detectors.

Applications:

The XD ventilation cross duct Natural Gas / CH₄ gas detectors are used to monitor for fugitive emissions, protect plant from the risk of explosion. These devices are typically mounted onto opposing side walls of ventilation ducting to provide earlier detection and fast activation of HVAC executive actions. The XD unit can also be used for applications where there is likely to be background concentrations of CH₄ and the objective is to detect significant changes to these levels e.g. salt cavern CH₄ storage applications.

- Oil & gas exploration rigs & FPSO's
- Oil & gas production platforms
- Petrochemical refineries
- Gas Turbine air inlets and ventilation
- Salt Cavern storage filling systems



Methane - Cross Duct Gas Detector (XD)

Features:

- Ultra narrow wavelength operation - Improved availability in heavy fog and rain compared to conventional, Infra Red devices
- SimuGas™ daily auto gas testing – No manual intervention or on-going cost for routine gas testing.
- Fastest speed of response (<1 second) – Increased safety by providing earlier warning.
- Increased sensitivity over conventional IR devices e.g 0-10,25 or 100% LEL -providing earlier detection & faster activation of HVAC executive actions.
- CH₄ specific – No false alarms from other hydrocarbon gases, as experienced with many other flammable gas detection technologies.

About Senscient ELDS™

Senscient's Enhanced Laser Diode Spectroscopy (ELDS™) product range builds upon the proven benefits of laser based gas sensing, taking this sensing principle to the next level. Patented technologies such as the Harmonic Fingerprint™ and SimuGas™ provide the highest levels of gas specificity, false alarm rejection and safety integrity in the most challenging operating conditions.

Detectable gases include: Methane (CH₄), Ethylene (C₂H₄), Ammonia (NH₃), Carbon Dioxide (CO₂), Hydrogen Sulphide (H₂S), Hydrogen Chloride (HCl), Hydrogen Fluoride (HF), and Multihydrocarbons (MHC). Other gases to be added.

Specifications:

Gas Ranges	Methane (CH ₄) 0-10% LEL 0-25% LEL 0-100% LEL
Path Length Format	0.5 - 5m Individual Transmitter (Tx) & Receiver (Rx)

Performance:

Response Time	T90 ≤ 1 second
Repeatability	<± 5% FSD
Linearity	<± 5% FSD

Environmental:

Ingress Protection	IP66/67 NEMA type 4/4X/6
Enclosure Material	316L stainless steel
Lens Material Tx	Faceted Optical Glass
Lens Material Rx	Aspheric Optical Glass
Operating Temperature	-55°C to +60°C (ambient)
Humidity	0 – 100% RH (non-condensing)
Vibration	10 – 150 Hz, 2 g
EMC	EN50270

Certification/Approvals:

CSA and UL

Class I Div 1 Groups B C & D T5
Class II Div 1 Groups E F & G T5
Class III Div 1
Ex d IIB + H₂ T5
Class I, Zone 1, AEx d IIB + H₂ T5
Tamb = -40°C to +60°C
Entry: ¾" NPT

ATEX / IECEx

II 2 GD Exd IIB + H₂ T5
Tamb -40°C to +60°C Gb
and Ex tb IIIC T100°C
Tamb = -40°C to +60°C Db IP66/67
Entry: M25

Customs Union of Russia, Kazakhstan & Belarus

EAC EX TR CU CoC
IExdIIBT5/H2X
Entry: M25

InMetro

Ex d IIB+H2 T5 Gb
ou
Extb IIIC T100°C Db IP66/67
Tamb: -40°C a +60°C
Entry: M25

Safety Integrity

Suitable for use in SIL2 Safety Systems per IEC 61508

Electrical:

Operating Voltage	Tx & Rx +24V DC, (+18 to +32V DC)
Power Consumption	Tx = 12 W (max), Rx = 10 W (max)
Outputs (Analog x 2)	4-20 mA, Configurable for 2 wire isolated or single wire, sink or source. Primary range on 4-20mA(1) Secondary range on 4-20mA(2), Note: Secondary range is typically greater than the primary. 3 mA (configurable 1 to 4 mA) 2.5 mA (configurable 0 to 3.5 mA) 2 mA (configurable 1 to 3.5 mA) 0.5 mA (configurable 0 to 1 mA) 21.5 mA (configurable 20 to 21.9 mA)
Low Signal Beam Block Inhibit Fault Over range	
Output (Digital x 2)	HART 7.1 & MODBUS RTU supported

Mechanical:

Size	Tx/Rx 140 mm dia. x 300 mm Mounting Plate (c/w fixing holes) Three size options 180mm x 180mm 250mm x 250mm 400mm x 400mm
Weight (Module) Weight (Mounting Plate)	Tx = 12.8 kg Rx = 13.8 kg 180 mm sq. 1.6 kg each 250 mm sq. 2.7 kg each 400 mm sq. 5.5 kg each
Mounting	Both Tx & Rx units require a mounting plate (ordered separately), for flat duct wall fixing. (Fixing bolts are not supplied).

Optical:

Uses HARMONIC FINGERPRINT™ to ensure no false alarms during adverse environmental conditions, misalignment or partial obscuration.

Alignment	± 2.5°
Obscuration	Operates up to 95%
Heated Optics	Tx & Rx lenses are continuously heated.
Laser Beam	Class 1 (Eye Safe) IEC 60825-1
FDA Accession No.	1410373-000 (For Imports into USA)

Calibration :

Factory calibrated for life, no routine calibration required.

Ordering Information:

To order / specify:	Senscient ELDS 1000 XD
Gas type:	CH ₄
Measuring Range:	e.g. 0-25% LEL
Path length:	0.5-5m
Certification:	e.g. ATEX
Mounting Plate:	e.g. 250mm x 250mm

Accessories:

Approved Interface terminal (PC)
Interface terminal (Tablet)
Alignment Adjustment Bushings
Gas Challenge Cell (Optional)

Distributed by:

